



Introducing Advanced Digital Versions
of the Reliable and Popular
Edose Metering Pump



NEO

Metering Pump



PRO
Metering Pump



BACKED BY A NATIONWIDE DEALER NETWORK
FOR PROMPT SALES AND SERVICE SUPPORT

 **INITIATIVE**
ENGINEERING



TM
NEO & PRO

Electronic Metering Pump

Standard Features



- Backlit LCD Display
- User friendly knob linked with digital display for adjusting dosing frequency
- Dosing head conveniently located next to front controls for easy maintenance access
- Built-in ARV with separate discharge point to prevent chemical spill on hands
- Double ball NRV
- Diaphragm made of solid PTFE to ensure maximum life
- Batch and Interval dosing features

Optional Advanced Features for NEO

- Level Switch Interlock
- 4 to 20 mA output
- Pulse Input
- Relay Output

Edose PRO



- Two line backlit LCD display
- All advanced features of the NEO model are standard in the PRO version
- Additionally a RS 485 MODBUS compatible output allows remote management and control



Tank Mounting Option

Wall Mounting Option

Technical Specifications

Dosing rate @ 4 kg /cm ²	1.5, 3.0, 6.0 & 10.0 lph
Suction/Discharge tubing	4/6 mm
Frequency	Up to 350 spm
Electrical	230 V AC, 50 Hz
Power consumption at 350 spm	30 Watts

Scope of Supply

- Pump
- Suction/ Discharge tubing
- Suction Filter with NRV
- Anti – siphon valve
- Mounting bolts
- O & M Manual

Also Available Edose Electronic Metering Pump



Sr. No. 273, Near Vitthal Mandir, Bhatewara Nagar,
Hinjewadi, Pune - 411 057, Maharashtra (India)
Tel.: +91 20 2293 2122, 2293 2123
email: info@initiativeengineering.com
www.initiativeengineering.com